

## Soustruhy > CNC > Hiturn 320

|                   |  |
|-------------------|--|
| Inv. číslo:       | 105771   |
| Typ:              | Hiturn 320   |
| Parametry:        | 320 mm, 800 mm   |
| Výrobce:          | Wemas  |
| Rok výroby/SO/GO: | 1999/-/-   |
| Lokalita:         | Německo  |
| Popis:            | Technical specifications: Turning diameter over bed 320 mm Turning diameter over cross support 150 mm Tip width 800 mm Spindle bore 50 mm Cone in the spindle - metric 60 Motor power at 1500 rpm 7.0 kW Spindle speed range Control system Heidenhain 1st row 0 - 1000 rpm. 2nd Row 20 - 4000 rpm. X-axis diameter of the lead screw 20 mm Leadscrew pitch 5 mm Max. Stroke 190 mm Rapid feed 7500 mm / min Max. Feed force 3000 N Accuracy of repeated position adjustment 0.008 mm Y-axis diameter of lead screw 25 mm Leadscrew pitch 5 mm Max. Stroke of the support carriage : 750 mm Rapid feed : 8000 mm / min Max. Feed force 5000 N Accuracy of repeated position adjustment 0.008 mm Tool head Multifix B max diameter of the steel 25 x 25 mm tailstock Pinhole diameter 65 mm Quill stroke 125 mm Cone of the quill Morse 4 Dimensions 2160 x 1594 x 1875 mm Weight approx 2150 kg With - HEIDENHAIN Manual Plus - Three-jaw lathe chuck - Multifix steel holder with 4 inserts used, in good condition |





